

Specifications of SheetHot[™] TF-100

Appearance/ Description	Single layer aluminium material Dimpled in one direction
Temperature Range Minimum Continuous Maximum Continuous Melting Point	-60°C 600°C 650°C
Thickness	1.8mm overall (0.45 material)
Weight	1.23 kg/m ²
Flexibility	Good
Flammability Rating	Non Flammable
Ignition Temperature (flash point)	No potential for ignition
RoHS	Yes
Halogen Free	Yes
Toxicity	Nil
Binders	No
Thermal Performance (Static)	Temperature Before (°C)Temperature After (°C)10027.712529.415031.517534.120036.422540.725046.727555.030066.032577.0

This data sheet and contained specifications exists solely for the user to determine the suitability of this product for specific use. The contents contained are derived from DCI testing procedures and Diver Metal Products PTY. LTD. makes no warranties as to their accuracy or completeness. Diver Metal Products PTY. LTD. will not be liable for any consequential or other damages arising from use or miss-use of their products





THERMAL & ACOUSTIC PRODUCTS DIVISION MANUFACTURERS OF HEAT AND NOISE MANAGEMENT PRODUCTS, THERMAL AND ACOUSTICS SHIELDS 45 TRAWALLA AVENUE, THOMASTOWN, VICTORIA 3074 Nat Ph: (03) 9357 2511 Nat Fax: (03) 9359 2191 Inter Ph: 61 3 9359 2191 Inter Fax: 61 3 9359 2191



