

Specifications of SheetHot[™] TF-600

Appearance/ Description	Six layer aluminium material Multi layered dimpled material	
Temperature Range Minimum Continuous Maximum Continuous Melting Point	-60°C 600°C 650°C	
Thickness	3.5mm Nominal	
Weight	2.1 kg/m ²	
Flexibility	Fair	
Flammability Rating	Non Flammable	
Ignition Temperature (flash point)	No potential for ignition	
RoHS	Yes	
Halogen Free	Yes	
Toxicity	Nil	
Binders	No	
Thermal Performance (Static)	-	mperature (°C) 19.6 19.7 19.8 20.1 20.3 20.8 21.2 22.0 22.8 23.8

This data sheet and contained specifications exists solely for the user to determine the suitability of this product for specific use. The contents contained are derived from DCI testing procedures and Diver Metal Products PTY. LTD. makes no warranties as to their accuracy or completeness. Diver Metal Products PTY. LTD. will not be liable for any consequential or other damages arising from use or miss-use of their products





THERMAL & ACOUSTIC PRODUCTS DIVISION MANUFACTURERS OF HEAT AND NOISE MANAGEMENT PRODUCTS, THERMAL AND ACOUSTICS SHIELDS 45 TRAWALLA AVENUE, THOMASTOWN, VICTORIA 3074 Nat Ph: (03) 9357 2511 Nat Fax: (03) 9359 2191 Inter Ph: 61 3 9359 2191 Inter Fax: 61 3 9359 2191



