



# DIVER CONSOLIDATED INDUSTRIES

PROPRIETOR DIVER METAL PRODUCTS PTY. LTD

## Specifications of SheetHot Extreme™ XT-5000

**Appearance/Description** Multi layer composite material  
Multi-directional dimpled

**Temperature Range**  
**Minimum Continuous** -60°C  
**Maximum Continuous** 1000°C  
**Melting Point** 1100°C

**Thickness** 2.8mm Nominal

**Weight** 2.54 kg/m<sup>2</sup>

**Flexibility** Poor

**Flammability Rating** Non Flammable

**Ignition Temperature (flash point)** No potential for ignition

**RoHS** Yes

**Halogen Free** Yes

**Toxicity** Nil

**Binders** No

Thermal Performance (Static)	Temperature Before (°C)	Temperature After (°C)
		100
	125	22.5
	150	23.0
	175	23.6
	200	24.3
	225	25.3
	250	26.7
	275	28.6
	300	33.2
	325	37.0

This data sheet and contained specifications exists solely for the user to determine the suitability of this product for specific use. The contents contained are derived from DCI testing procedures and Diver Metal Products PTY. LTD. makes no warranties as to their accuracy or completeness. Diver Metal Products PTY. LTD. will not be liable for any consequential or other damages arising from use or miss-use of their products



**THERMAL & ACOUSTIC PRODUCTS DIVISION**  
MANUFACTURERS OF HEAT AND NOISE MANAGEMENT PRODUCTS,  
THERMAL AND ACOUSTICS SHIELDS  
45 TRAWALLA AVENUE, THOMASTOWN, VICTORIA 3074  
Nat Ph: (03) 9357 2511 Nat Fax: (03) 9359 2191  
Inter Ph: 61 3 9359 2191 Inter Fax: 61 3 9359 2191

