



DIVER CONSOLIDATED INDUSTRIES

PROPRIETOR DIVER METAL PRODUCTS PTY. LTD

Specifications of QuietSheet™ Exterior

Appearance/ Description	Polyester blanket with needle punched aluminium foil, with perforated aluminium top cover
------------------------------------	---

Temperature Range	
Minimum	-60°C
Continuous	200°C
Maximum Continuous	260°C
Melting Point	

Thickness	10mm Nominal
------------------	--------------

Weight	2.25 kg/m ²
---------------	------------------------

Flexibility	Poor
--------------------	------

Flammability	Polyester -Self extinguishing upon ignition
---------------------	---

Ignition Temperature (flash point)	>260°C
---	--------

RoHS	Yes
-------------	-----

Halogen Free	Yes
---------------------	-----

Toxicity	Nil
-----------------	-----

Binders	No
----------------	----

Acoustic Absorption Coefficients	Frequency (Hz)	Coefficient
	125	0.03
	250	0.07
	500	0.15
	1000	0.27
	2000	0.40
	4000	0.48

This data sheet and contained specifications exists solely for the user to determine the suitability of this product for specific use. The contents contained are derived from DCI testing procedures and Diver Metal Products PTY. LTD. makes no warranties as to their accuracy or completeness. Diver Metal Products PTY. LTD. will not be liable for any consequential or other damages arising from use or miss-use of their products



THERMAL & ACOUSTIC PRODUCTS DIVISION
MANUFACTURERS OF HEAT AND NOISE MANAGEMENT PRODUCTS,
THERMAL AND ACOUSTICS SHIELDS
45 TRAWALLA AVENUE, THOMASTOWN, VICTORIA 3074
Nat Ph: (03) 9357 2511 Nat Fax: (03) 9359 2191
Inter Ph: 61 3 9359 2191 Inter Fax: 61 3 9359 2191

